

# ATLANTIC 1650

## New Hot & Cold laminator

### THERMAL LAMINATION

- Use of thermal encapsulation films up to 320 microns

### COLD LAMINATION




- Single side lamination with or without waste paper
- Simultaneous single side lamination and adhesive mounting
- Encapsulation with cold film in one run
- Application tape
- Colour background using colour vinyl
- Mounting onto boards up to 50 mm (2") thickness



Speed up to 6,20 m/mn (21 ft/mn)  
Mounting up to 50 mm (2") thick.  
Hi-capacity hot and cold laminator up to 140°C (280°F)  
Working width 165 cm (65")



## Specifications

 Mounting up to 50 mm (2")	 10 speed	 Diameter 23 cm (9"), film reel 100 m (110 yd)	<h3>Atlantic 1650</h3>
Maximum thickness document + board			50 mm (2")
Maximum working width			171 cm (67")
Maximum film width			165 cm (64")
Maximum length of the film reels			100 m (maximum diameter 23 cm/9")
Diameter of the rollers			maximum 120 mm (4.7")
Temperature			independant heat on top and bottom up to 140°C
Heating time from 20°C to 100°C			30 mn
Number of self blocking shaft delivered			5 + 1 unwinding shaft
Adjustable speed m/mn			from 0,3 to 6,3
Adjustable speed ft/mn			from 0,9 to 21
Power W			3600
Voltage			230 V / 50-60 Hz
Amperage			16A/230 V
Dimensions of the machine	(cm) (inch)	W 206 x D 82 x H 153 W 81" x D 32" x H 60"	
Net weight of the machine			300 kg
Shipping dimensions of the machine	(cm) (inch)	W 213 x P93 x H 170 L 84" x P 37" x H 66"	
Machine weight for shipping			370 kg
Warranty			1 year
Made in France, CE certified in compliance with the Machine and the Electromagnetic Compatibility Directives CEM.			✓

Roll to Roll system delivered as standard with the machine.



RoHS



www.kala.fr